



MOUNTING HOLE

1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-18 GHz
- 1.2 NOMINAL IMPEDANCE: 50 OHMS
- 1.3 VOLTAGE RATING: 500 VOLTS MAX.
- 1.4 VSWR: 1.23 MAX.

2.0 MATERIALS

- 2.1 BODIES: BRASS PER JIS-C3604
- 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

3.0 FINISHES AND OTHERS

- 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL

- 4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348A

5.0 ENVIRONMENTAL

- 5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C

6	O-RING	SILICONE	1	RED
5	INSULATION	TEFLON	1	NONE
4	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 50 μ " MIN.
3	BODY	BRASS	1	GOLD 3 μ " MIN.
2	WASHER	BRASS	1	GOLD
1	NUT	BRASS	1	GOLD
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

DESCRIPTION		STRAIGHT SMA BULKHEAD JACK-JACK ADAPTER						
製圖	DRAWN	TOLERANCE	品名	40191201900005	日期	DATE	版次	REV.
	<i>Amy</i>					.X		
檢圖	CHECK	單位	SCALE	DWG.NO.	19-0149	佳楠精密電子股份有限公司 CHIN NAN PRECISION ELECTRONICS CO.,LTD.		
	<i>Leona</i>							
認定	APPROVAL	ANGLE	比例					
	<i>Jenny</i>							