



**1.0 ELECTRICAL**

- 1.1 FREQUENCY RANGE: DC-4 GHz
- 1.2 NOMINAL IMPEDANCE: 50 OHMS
- 1.3 VOLTAGE RATING: 500 VOLTS MAX.
- 1.4 VSWR: 1.3 MAX.

**2.0 MATERIALS**

- 2.1 BODIES: BRASS PER JIS-C3604
- 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

**3.0 FINISHES AND OTHERS**

- 3.1 SEE BELOW TABLE FOR DETAILS.

**4.0 MECHANICAL**

- 4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348B

**5.0 ENVIRONMENTAL**

- 5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C

6	CHASSIS	BRASS	1	NICKEL 100 μ" MIN.
5	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 3 μ" MIN.
4	INSULATION	TEFLON	1	NONE
3	WASHER	BRASS	1	NICKEL 100 μ" MIN.
2	INSULATION	TEFLON	1	NONE
1	BODY	BRASS	1	NICKEL 100 μ" MIN.
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

DESCRIPTION		BNC RIGHT ANGLE PCB MOUNT JACK RECEPTACLE							
製圖	DRAWN	TOLERANCE		品名	40130408300030	日期	DATE	版次	REV.
	Jackie	.X	±0.2	TITLE	ROHS COMPLIANT (50Ω)	08.14.18'		A-0	
檢圖	CHECK	.XX	±0.1	單位	mm(in)	DWG.NO. 13-0705			
	Arc	.XXX	±0.05	比例	SCALE	3:1			
認定	APPROVAL	ANGLE ±5°				<b>佳楠精密電子股份有限公司</b> CHIN NAN PRECISION ELECTRONICS CO.,LTD.			
	Jenny								