



MOUNTING HOLE  
SCALE 2:1

- 1.0 ELECTRICAL
  - 1.1 FREQUENCY RANGE: DC-4 GHz
  - 1.2 NOMINAL IMPEDANCE: 50 OHM
  - 1.3 VOLTAGE RATING: 500 VOLTS MAX.
  - 1.4 VSWR: 1.5 MAX.
- 2.0 MATERIALS
  - 2.1 BODIES: BRASS PER JIS-C3604
  - 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
  - 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
- 3.0 FINISHES AND OTHERS
  - 3.1 SEE BELOW TABLE FOR DETAILS.
- 4.0 MECHANICAL
  - 4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348A
- 5.0 ENVIRONMENTAL
  - 5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C
  - 5.2 CONNECTOR MUST WITHSTAND WATERPROOF LEAK TEST PRESSURE 7kg/cm<sup>2</sup> MIN.

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
9	CENTER CONTACT	BERYLLIUM COPPER	2	GOLD 3μ" MIN.
8	CHASSIS	BRASS	1	NICKEL 100μ" MIN.
7	HERMETICALLY SEALED	---	1	NONE
6	BODY	BRASS	1	NICKEL 100μ" MIN.
5	INSULATION	TEFLON	2	NONE
4	WASHER	BRASS	1	NICKEL
3	GASKET	SILICONE	1	RED
2	WASHER	STEEL	1	NICKEL
1	NUT	BRASS	1	NICKEL 100μ" MIN.

DESCRIPTION		BNC STRAIGHT BULKHEAD JACK-JACK ADAPTER HERMETICALLY SEALED	
DRAWN	TOLERANCE	品名	40131201300026
Jackie	.X	TITLE	\ROHS COMPLIANT (500)
CHECK	±0.2	單	UNIT
Jenny	.XX	位	mm(in)
APPROVAL	±0.1	比	SCALE
Jenny	.XXX	例	3:1
DATE	05.22.12	DWG.NO	13-0625
REV.	A-5		



佳楠精密電子股份有限公司  
CHIN NAN PRECISION ELECTRONICS CO., LTD.