



STRIPPING DIMENSION

**1.0 ELECTRICAL**

- 1.1 FREQUENCY RANGE: DC-12.4 GHz
- 1.2 NOMINAL IMPEDANCE: 50 OHMS
- 1.3 VOLTAGE RATING: 250 VOLTS MAX.
- 1.4 VSWR: 1.15 MAX. @3 GHz  
1.25 MAX. @6 GHz  
1.52 MAX. @12.4 GHz

**2.0 MATERIALS**

- 2.1 BODIES: BRASS PER JIS-C3604  
BERYLLIUM COPPER PER ASTM B196 UNS C17300
- 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

**3.0 FINISHES AND OTHERS**

- 3.1 SEE BELOW TABLE FOR DETAILS.

**4.0 MECHANICAL**

- 4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348B
- 4.2 FOR USE WITH RG405 OR SIMILAR STYLE CABLE
- 4.3 CABLE ATTACHMENT: OUTER: SOLDER, INNER: SOLDER

**5.0 ENVIRONMENTAL**

- 5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C



佳楠精密電子

6	CAP	BRASS	1	GOLD 5 μ" MIN.
5	CHASSIS	BRASS	1	GOLD 5 μ" MIN.
4	BODY	BERYLLIUM COPPER	1	GOLD 5 μ" MIN.
3	INSULATION	TEFLON	1	NONE
2	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 30 μ" MIN.
1	SHELL	BRASS	1	GOLD 5 μ" MIN.
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

DESCRIPTION		SSMB RIGHT ANGLE PLUG SOLDER							
製圖	DRAWN	TOLERANCE	品名	40460308220001	RG405 (50Ω)	日期	DATE	版次	REV.
	Leona								
檢圖	CHECK	單位	UNIT	DWG.NO.	46-0033	佳楠精密電子股份有限公司 CHIN NAN PRECISION ELECTRONICS CO.,LTD.			
	Jenny								
認定	APPROVAL	比例	SCALE	佳楠精密電子股份有限公司 CHIN NAN PRECISION ELECTRONICS CO.,LTD.					
	Jenny								
		ANGLE	±5°						