

PRODUCT SPECIFICATIONS

BNC Straight Jack Crimp For RG 174 or RG 316 or RG188 or LMR 100A Cable

[40130208005032](#)



Electrical

Impedance	50 Ω
Frequency Range	DC-4 GHz
V.S.W.R	1.22 max.
Insertion Loss	0.2 dB max. @3GHz
Voltage Rating	500 volts rms. at sea level
Dielectric Withstanding Voltage	1500 volts rms. at sea level
Insulation Resistance	5000 Megohms min.
Contact Resistance	Center contact = 1.5 Milliohms max. Outer contact = 0.2 Milliohms max.
Power Handling	500W

Mechanical

Mechanical	Bayonet locking
Durability	500 Cycles
Cable Retention	15 lbs min.
Center Contact Retention	6 lbs min. Axial force

Material

Connector Body	Brass
Center Contact	Beryllium Copper, Brass
Insulation	PTFE


Environmental

Temperature	-65°C to 165°C
Vibration	Refer to MIL-STD-202 Method 204 Test Cond. B.
Salt Spray	Refer to MIL-STD-202 Method 101 Test Cond. B.

Related Documents

Assembly Instructions	CM-03
-----------------------	-------

Test Report



CH 1 - S11
0.0000 mm REF
0.000 dB OFFSET
0.00° OFFSET

MARKER 1
1.322762250 GHz
1.075 U

▶ MARKER TO MAX
MARKER TO MIN

MARKER READOUT
FUNCTIONS