

PRODUCT SPECIFICATIONS

TNC Straight Bulkhead Jack Clamp for RG58, RG142, RG400, LMR195 Cable

[40150208109002](#)



Electrical

Impedance	50 Ω
Frequency Range	DC- 11 GHz
V.S.W.R	1.3 MAX
Insertion Loss	0.18 dB max.@9GHz
Voltage Rating	500 volts rms. at sea level
Dielectric Withstanding Voltage	1500 volts rms. at sea level
Insulation Resistance	5000 Megohms min
Contact Resistance	Center contact = 1.5 Milliohms max. Outer contact = 0.2 Milliohms max.
Power Handling	500W

Mechanical

Mechanical	7/16" -28 Threaded coupling
Durability	500 Cycles
Cable retention	40 lbs min.
Center contact retention	6 lbs min. Axial force
Torque	NONE
Recommended Torques	NONE
Panel nut	35~40 inch-lbs
Clamp nut	26~30 inch-lbs

Material

Connector Body	Brass
Center Contact	Beryllium Copper
Insulation	PTFE
Gasket	Silicone

Environmental

Temperature	-65°C to 165°C
Vibration	Refer to MIL-STD-202 Method 204 Test Cond. B.
Salt Spray	Refer to MIL-STD-202 Method 101 Test Cond. B.

Related Documents

Assembly instructions	CM-07
-----------------------	-------

Test Report


S11 FORWARD REFLECTION

FGT

SWR

REF=1.000 U

100.000 mU/DIV



CH 1 - S11
0.0000 mm REF
0.000 dB OFFSET
0.00° OFFSET

MARKER 2
7.987300000 GHz
1.205 U

▶ MARKER TO MAX
MARKER TO MIN

1 11.018050000 GHz
1.136 U

MARKER READOUT
FUNCTIONS