

PRODUCT SPECIFICATIONS

SMB Right Angle Jack Crimp For RG 174 Or RG 316 Or RG188 Or LMR100 Cable

40240408005003



Electrical

Impedance	50 Ω
Frequency Range	DC-4 GHz
V.S.W.R	1.22 max.
Insertion Loss	0.2 dB max.
Voltage Rating	335 volts rms. at sea level
Dielectric Withstanding Voltage	1000 volts rms. at sea level
Insulation Resistance	1000 Megohms min.
Contact Resistance	Center contact = 6.0 Milliohms max. Outer contact = 1.0 Milliohms max.
Power Handling	220W

Mechanical

Mechanical	Snap-on coupling
Durability	500 Cycles
Cable Retention	15 lbs min.
Center Contact Retention	4 lbs min. Axial force

Material

Connector Body	Brass
Center Contact	Brass
Insulation	PTFE

Environmental

Temperature	-65°C to 165°C
Vibration	Refer to MIL-STD-202 Method 204 Test Cond. B.
Salt Spray	Refer to MIL-STD-202 Method 101 Test Cond. B.

Related Documents

Assembly instructions	CM-06
-----------------------	-------

Test Report

S11 FORWARD REFLECTION

FGT

SWR


REF=1.000 U

100.000 mU/DIV

CH 3 - S11
0.0000 mm REF
0.000 dB OFFSET
0.00° OFFSET

MARKER 1
1.371550000 GHz
1.017 U

▶ MARKER TO MAX
MARKER TO MIN



MARKER READOUT
FUNCTIONS