

# PRODUCT SPECIFICATIONS

## SSMB Right Angle Plug Crimp For RG 174 Or RG 316 Or RG188 Or LMR100 Cable

40460308005003



### Electrical

Impedance	50 Ω
Frequency Range	DC-12.4 GHz
	1.15 max. @3GHz
V.S.W.R	1.25 max. @6GHz
	1.52 max. @12.4GHz
Insertion Loss	0.3 dB max. @4GHz
Voltage Rating	250 volts rms. at sea level
Dielectric Withstanding Voltage	500 volts rms. at sea level
Insulation Resistance	1000 Megohms min.
Contact Resistance	Center contact = 4.0 Milliohms max. Outer contact = 1.0 Milliohms max.
Power Handling	125W

### Mechanical

Mechanical	Snap-on coupling
Durability	500 Cycles
Cable Retention	15 lbs min.
Center Contact Retention	2 lbs min. Axial force

### Material

Connector Body	Brass, Beryllium Copper
Center Contact	Beryllium Copper
Insulation	PTFE

### Environmental

Temperature	-65°C to 165°C
Vibration	Refer to MIL-STD-202 Method 204 Test Cond. B.
Salt Spray	Refer to MIL-STD-202 Method 101 Test Cond. B.

### Related Documents

Assembly Instructions	CM-06
-----------------------	-------

# Test Report

