

PRODUCT SPECIFICATIONS

SSMB Right Angle Plug Solder For RG 405U Cable

40460308220001



Electrical

Impedance	50 Ω
Frequency Range	DC-12.4 GHz
	1.15 max. @3 GHz
V.S.W.R	1.25 max. @6 GHz
	1.52 max. @12.4 GHz
Insertion Loss	0.3 dB max. @4 GHz
Voltage Rating	250 volts rms. at sea level
Dielectric Withstanding Voltage	500 volts rms. at sea level
Insulation Resistance	1000 Megohms min.
Contact Resistance	Center contact = 4.0 Milliohms max. Outer contact = 1.0 Milliohms max.
Power Handling	125W

Mechanical

Mechanical	Snap-on coupling
Durability	500 Cycles
Cable Retention	30 lbs min.
Center Contact Retention	2 lbs min. Axial force

Material

Connector Body	Brass, Beryllium Copper
Center Contact	Beryllium Copper
Insulation	PTFE

Environmental

Temperature	-65°C to 165°C
Vibration	Refer to MIL-STD-202 Method 204 Test Cond. B.
Salt Spray	Refer to MIL-STD-202 Method 101 Test Cond. B..

Related Documents

Assembly Instructions	CM-02
-----------------------	-------

Test Report

