

SMA 27G

Straight Plug Solder for RG402 Cable

40520108219001(52-01W-TGG)



Electrical

Impedance	50 Ω
Frequency Range	DC to 26.5 GHz 1.16 max@18 GHz
V.S.W.R	1.2 max. @26.5 GHz
Voltage Rating	500 volts rms. at sea level
Dielectric Withstanding Voltage	1,000 volts rms. at sea level
Insulation Resistance	5,000 Megohms min.
Contact Resistance	Center contact = 3.0 Milliohms max. Outer contact = 2.0 Milliohms max.
Power Handling	500W

Mechanical

Mechanical	1/4"-36 Threaded coupling
Durability	500 Cycles
Torque	15 in-lbs min.
Recommended Torques	7~10 inch-lbs

Material

Connector Body	Stainless Steel
Center Contact	Beryllium Copper
Insulation	PTFE
Gasket	Silicone

Environmental

Temperature	-65°C to 165°C
Vibration	Refer to MIL-STD-202 Method 204 Test Cond. D.
Salt Spray	Refer to MIL-STD-202 Method 101 Test Cond. B.

Related Documents

Assembly instructions	<u>CM-18</u>
-----------------------	------------------------------

Test Report


S11 FORWARD REFLECTION

FGT

SWR

REF=1.000 U

100.000 mU/DIV



CH 1 - S11
0.0000 mm REF
0.000 dB OFFSET
0.00° OFFSET

MARKER 1
18.002100000 GHz
1.083 U

MARKER TO MAX
MARKER TO MIN

2 26.528200000 GHz
1.108 U

MARKER READOUT
FUNCTIONS